

# M27

      
Width    Depth    Ratio    Length    Weight

|     | mm   | mm   | kg/m | m    | kg |
|-----|------|------|------|------|----|
| 135 | 11.0 | 1.85 | 5.20 | 9.6  |    |
| 142 | 12.0 | 1.97 | 5.17 | 10.2 |    |
| 152 | 13.0 | 2.33 | 5.19 | 12.1 |    |
| 160 | 13.0 | 2.51 | 5.21 | 13.1 |    |
| 170 | 13.0 | 2.65 | 5.17 | 13.7 |    |
| 180 | 15.0 | 2.89 | 5.22 | 15.1 |    |
| 188 | 15.0 | 3.01 | 5.22 | 15.7 |    |
| 194 | 15.0 | 3.23 | 5.20 | 16.8 |    |
| 205 | 16.0 | 3.58 | 5.20 | 18.6 |    |
| 210 | 16.0 | 3.63 | 5.15 | 18.7 |    |
| 220 | 16.0 | 3.95 | 5.22 | 20.6 |    |
| 230 | 15.0 | 3.99 | 5.26 | 21.0 |    |
| 240 | 15.0 | 4.28 | 5.19 | 22.2 |    |
| 250 | 16.0 | 4.45 | 5.24 | 23.3 |    |
| 290 | 13.5 | 4.62 | 5.15 | 23.8 |    |



**APPLICATION:** On all-steel tires for all wheels on light-duty truck, city bus, mini-bus, tour bus and van

**FEATURE:**

1. High wearability, long mileage
2. Good heat dispersion, fitting for long-distance vehicle
3. Fit for all wheels

